



Clear Opening [CO] / Lichte Weite (mm)	Ø 344
Percentage of raised pattern / Erhabene Flaechе	-
Outlet Area / Auslassbereich (cm <sup>2</sup> )	929
Inlet Area / Einlaufquerschnitt (cm <sup>2</sup> )	1406

○ = Test dimension/Pruefmaß

local article number: 1212373

for missing dimensions see 3D model

001	MH03181: First creation / Erstmalige Erstellung	sgadagi	05.06.2024
-----	---	---------	------------

index: modification:		author:		date:	
material number:	old article number:	general tolerance: ISO 8062-3-DCTG-12 / ISO 2768-mK	surface: Deburred	weight: 65.3 kg	doctype: P
ACO <b>ACO Passavant Detego GmbH</b> Scheidetalstraße 3 65326 Aarbergen www.aco-passavant-guss.de		basic material:	welding tolerance	projection: ISO-E 	format: A3
created by: tmeuer		reviewed by: tmeuer		sorting number:	scale: 1:5

title:  
**Brückenentwässerung**  
 Bridge restoration top 500x500, D 400, SW41.5 mm, DS  
 Brückensanieraufsatz 500x500, D 400, SW41.5 mm, PF

**serial-released**  
Solidworks

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. Observe copyright by ISO 16016	drawing-no.: <b>1436311</b>	index: <b>001</b>	release date: <b>21.06.2024</b>	sheet: <b>1/1</b>
--	--------------------------------	----------------------	------------------------------------	----------------------

Deburred / Geputzt  
 (Rz 25)

Ø 10 H12  
 Drilled during the assembly /  
 Bei der Montage gebohrt